

# MIGRATORY CORROSION INHIBITOR (MCI®) PRODUCTS FOR CONCRETE



## MCI®-2006



### PRODUCT DESCRIPTION

MCI®-2006 is a concrete admixture in powdered form. MCI®-2006 contains MCI®s (Migratory Corrosion Inhibitors) to protect reinforcing steel, galvanized steel and other metals embedded in concrete from corrosion induced by carbonation, chloride and atmospheric attack. MCI®-2006 protects with a time proven migratory inhibitor function. In addition, it contains a proven contact inhibitor. When incorporated into the concrete mix, MCI®-2006 reduces the chloride ingress, seeks out and forms a corrosion inhibiting protective layer on metal reinforcement.

### WHERE TO USE

MCI®-2006 is recommended for:

- All reinforced, precast, prestressed, post tensioned or marine concrete structures.
- Steel-reinforced concrete bridges, highways and streets exposed to corrosive environments (carbonation, deicing salts and atmospheric attack).
- Parking decks, ramps and garages.
- All reinforced marine concrete structures.
- Concrete piers, piles, pillars, pipe and utility poles.
- Restoration and repair of all reinforced concrete commercial and civil engineered structures.

### ADVANTAGES

MCI®-2006 offers engineers, owners, contractors, DOTs and government agencies a time proven corrosion inhibiting technology that will extend the life of all reinforced concrete structures.

- Protects against the harmful effects of corrosion even in the densest concrete.
- Reduces the chloride ingress.
- Does not contain any calcium nitrite.
- Non-hazardous and non-toxic.
- Non-flammable.
- Organic, safe and environmentally friendly.
- Technology is lab and field tested worldwide.
- Concentrated for cost effectiveness on all projects.
- Protects both anodic and cathodic areas.
- Will migrate to adjacent areas to protect surrounding metals.
- NSF Standard 61 approved for potable water applications (certified by Underwriters Laboratories).

### TYPICAL PROPERTIES

Appearance	White to off-white powder
pH	5.5-6.5 (1% aqueous)

### DOSAGE

Added to the concrete mix at the rate of 1 pound per cubic yard (0.6 kg/cubic meter).

### APPLICATION

MCI®-2006 can be added to concrete at the ready-mix plant, directly to the ready-mix truck drum or to portable mixers. Concrete should be mixed thoroughly.

### LIMITATIONS

MCI®-2006 will act as a retarding admixture. It retards setting time up to four hours compared to a control. A non-chloride accelerator may be used to offset retardation.

### PACKAGING AND STORAGE

MCI®-2006 is available in 5 lbs. (2.3 kg), 50 lbs. (22.7 kg), and 100 lbs. (45.3 kg) packages. Store product in a cool dry place. Shelf life is 24 months in sealed container.



**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



Distributed by:


4119 White Bear Parkway, St. Paul, MN 55110 USA  
 Phone (651) 429-1100, Fax (651) 429-1122  
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
 Internet http://www.CortecVpCI.com

printed on recycled paper 10% post consumer

Revised 8/25/03. Cortec Corporation 2001-2003. All rights reserved. Supersedes: 4/8/02  
 Cortec®, MCI®, and VpCI® are trademarks of Cortec Corporation



Certificate No.70781



Certificate No.81867