

MIGRATORY CORROSION INHIBITOR™ (MCI®) PRODUCTS FOR CONCRETE



MCI®-2020 Powder & MCI®-2020 V/O Powder



PRODUCT DESCRIPTION

MCI®-2020 Powder is a water-soluble migratory corrosion inhibitor for the treatment of existing concrete structures. It is designed to migrate through even the densest of structures and seek out embedded steel reinforcing bars. MCI®-2020 Powder also protects a multitude of other metals including carbon steel, galvanized steel and aluminum. The unique feature of Migrating Corrosion Inhibitors (MCI®) is that even if not in direct contact with metals, the inhibitor will migrate a considerable distance through concrete to provide protection. MCI®-2020 Powder will reduce corrosion of reinforcing metals and extend the service life of the structure. A special version of MCI®-2020 Powder - MCI®-2020 V/O Powder is designed for vertical and overhead applications.

WHERE TO USE

MCI®-2020 Powder is recommended for:

- All reinforced, precast, prestressed, post-tensioned or marine concrete structures
- Steel-reinforced concrete bridges, highways and

- viaducts exposed to corrosive environments (carbonation, deicing salts and atmospheric attack)
- Parking decks, ramps and garages
- Preventive maintenance of all reinforced commercial and civil engineered concrete structures
- Concrete piers, dams, offshore platforms, piles, pillars, pipes and utility poles
- Restoration and repair of all reinforced concrete commercial and civil engineered structures
- Plant floors subject to chemical and/or acid attack
- Buildings and foundations of all types
- Cooling towers and potable water tanks

ADVANTAGES

- MCI®-2020 Powder offers engineers, owners, contractors, DOTs and government agencies a time proven corrosion inhibiting technology that will extend the life of all reinforced concrete structures
- Protects against the harmful effects of corrosion by migrating into even in the densest concrete
- Migratory inhibitors reduce further corrosion of rusted metals
- Once diluted, easily applied by spray, roller, squeegee or paint brush to any concrete surface, reducing the high cost of labor and equipment
- Does not contain any calcium nitrite
- Water-soluble and non-flammable for easy handling
- Does not require the removal of sound concrete
- Organic, safe and environmentally friendly
- Enhances the durability of reinforced concrete
- Lab and field tested worldwide
- Allows concrete to breathe and vapor to diffuse, is not a vapor barrier
- Protects both anodic and cathodic areas of reinforcing steel (or metal)
- Proven effective in the Strategic Highway Research Program (SHRP) funded by the federal government and state DOTs



- Confirmed effective in international documented field evaluation (ASTM G-109, Industrial Standards (IS) Japan and Korea, etc.)
- Proven to migrate and protect reinforced concrete in adjacent areas
- No cure time is required - traffic may resume minutes after application if necessary
- Non-hazardous, 100% concentrated product, thus economical and convenient for all types of transportation

COVERAGE AFTER 1:4 DILUTION IN WATER

150 ft²/gal (3.68 m²/L). Dense substrates may require two coats at the rate of 300 ft²/gal (5.52 m²/L).

PACKAGING

MCI®-2020 Powder is available in 100 pound (45 kg) bags.

SURFACE PREPARATION

Surface should be dry, sound, clean and free of all dirt, oil, grease efflorescence, sealers, coatings, membranes and asphalt. Cleaning may be done by steam cleaning, water-blasting or sandblasting.

APPLICATION

Before application, dissolve MCI®-2020 Powder in fresh tap water in a 1:4 ratio by weight or 1 bag per 55 gallon (208 liter) drum. For MCI®-2020 V/O Powder mixing time 30-40 minutes required to establish right viscosity. Apply the solution by spray (conventional airless or hand pressure spray equipment), roller, squeegee or paint brush to any concrete surface. Dense substrates may require two coats with a minimum of 8 hours between coats. The surface should be rinsed with water, pressure washed or blast-cleaned to remove any residue prior to applying a sealer, coating, repair mortar or concrete overlay.

LIMITATIONS

The solution of 1:4 MCI®-2020 Powder and MCI®-2020 V/O Powder with water should be kept above freezing and below 125°F (50°C). Do not apply if the temperature is expected to fall below freezing within 12 hours. MCI® will not penetrate film-forming sealers, coatings, paints, membranes or asphalt.

PHYSICAL PROPERTIES

(for MCI®-2020 Powder & MCI®-2020 V/O Powder)

Appearance	White to Light Blue powder
pH	6.5-7.5 (1% aqueous)
Storage/Shelf Life	24 months in sealed drums
Alkalinity Test	600 mg/L

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet <http://www.CortecVpCI.com>

Distributed by:



printed on recycled paper 10% post consumer

Revised 6/05/02, Cortec Corporation 2002. All rights reserved. Supersedes: 5/7/01. MCI® is a trademark of Cortec Corporation.

Certificate No.70781

Certificate No.81867