

MIGRATORY CORROSION INHIBITOR™ (MCI®) PRODUCTS FOR CONCRETE



MCI® -2026 Flooring System

MCI® -2020

MCI® -2020 is a corrosion inhibitor formulated to migrate through the concrete, seeking out and attaching itself to the surface of reinforcing steel. Apply MCI® -2020 by low pressure spray or brush onto the prepared surface until it soaks into the concrete in a time frame of 7.5 - 24 hours.

Important: If overdose of MCI® -2020 occurs, it is necessary to rinse the concrete surface before application of MCI® -2026 Concrete Primer.

MCI® -2026 Concrete Primer

MCI® -2026 Concrete Primer coating is a water-based, 2-component, epoxy coating that outperforms and outlasts most solvent-based sealers without the associated odors, flammability, or VOC's. MCI® -2026 Concrete Primer meets all of the USDA guidelines for use in federally inspected poultry and meat plants. MCI® -2026 Concrete Primer is available in clear, gray and other colors. MCI® -2026 Concrete Primer can be used as a part of MCI® -2026 flooring system or as a top coat.

MCI® -2026 Floor Coating

MCI® -2026 Floor Coating is a 100% solids, 2-component, novolac epoxy coating designed for environments that require a high degree of chemical or temperature resistance. MCI® -2026 Floor Coating meets all of the USDA guidelines for use in federally inspected poultry and meat plants. MCI® -2026 Floor Coating is available in clear, gray and a selection of colors.

Important: Allow the MCI® -2026 Concrete Primer to dry before mixing and applying the next coating. The primed floor should be tack free and clear in appearance. This will vary with temperature and humidity but is normal between 2-5 hours at 75°F (24°C) and 50% R.H.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
 Internet <http://www.cortecvci.com>

Distributed by:



printed on recycled paper 10% post consumer

Revised 8/21/02. Cortec Corporation 2002. All rights reserved. Supersedes: 8/12/02. MCI® is a registered trademark of Cortec Corporation.



Certificate No.70781

Certificate No.81867