

# MIGRATORY CORROSION INHIBITOR™ (MCI®) PRODUCTS FOR CONCRETE



## MCI-2060

### PRODUCT DESCRIPTION

MCI-2060 is a cleaner and degreaser that contains Migratory Corrosion Inhibitors™ (MCI®s). It effectively cleans caked on grease, dirt, oil and mud on concrete driveways, garage floors, walkways and curbs, making them look like new. MCI-2060 contains inhibitors which migrate into concrete, providing protection to rebars and all metals in contact with concrete.

### FEATURES

- Good for various oils and greases
- Will not damage sealed or painted surfaces
- Non-flammable
- Remains active even if left to dry
- Non-toxic and biodegradable
- May be used at room temperature to reduce energy consumption
- Viscous liquid will cling to ceilings and vertical surfaces in a ready-to-use formulation
- Replaces caustic-based and strong acid-based concrete cleaners
- No special protective equipment needed for application
- Provides corrosion protection for rebars and all metals which are in contact with concrete
- Adjacent areas do not need special protection during application
- Removes cosmoline, transit coatings, and sludge

### TYPICAL APPLICATIONS

- Removal of oils, greases, dirt from all concrete and ceramic surfaces
- Cleaning/degreasing of sealed or painted concrete surfaces

### APPLICATION

*For cleaning:*

1. Brush, roll or spray MCI-2060 onto a concrete surface.
2. Use a deck brush to agitate the surface.
3. Allow MCI-2060 time to clean. Depending on how soiled the surface is, it may take several minutes to one hour.
4. Rinse the loosened grime from the concrete surface using water. If possible, use a pressure washer. Floors may also be flooded with water and the debris brushed away or wet-vacuumed up.

### TYPICAL PROPERTIES

Appearance	Clear light yellow liquid
Density	8.6-8.7 lb/gal (1.03-1.04 kg/l)
pH	11-12 (Neat)
Non-volatile Content	18-25%
Usage	1% up to concentrate

### LIMITATIONS

Migrating Corrosion Inhibitors™ are unable to penetrate through a sealer or coating. MCI-2060 can only protect reinforcing metal when applied to bare concrete or directly onto the metal.

### PACKAGING AND STORAGE

MCI-2060 is available in 5 gallon (19 liter) plastic pails and 55 gallon (208 liter) metal drums, liquid totes and bulk. Store between 32°F (0°C) and 120°F (49°C).

Migratory Corrosion Inhibitors™ (MCI®) is a registered trademark of Cortec Corporation.

**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
Internet <http://www.cortecvci.com>

