




## SURFACE PREPARATION PRODUCTS

# VpCI-418 Heavy Duty Alkaline Cleaner VpCI-418 LM



### DESCRIPTION

VpCI-418L/418LM are non-foaming, heavy-duty alkaline cleaners/degreasers for cleaning industrial, oil field, commercial and marine equipment. VpCI-418L/418LM are designed for use in power washing machinery, high agitation parts washers and high-pressure spray washers.

VpCI-418L/418 LM are non-flammable, nitrite-free, non-toxic and do not present disposal problems associated with most phosphate cleaners.

VpCI-418L/418LM contain inhibitors to protect metal parts from corrosion after cleaning. They have a unique ability to remove difficult deposits such as heavy hydrocarbons, greases, drawing and buffing compounds, and mill and machinery oils.

### FEATURES

- Heavy-duty alkaline cleaner and degreaser with unique cleaning action for removing hydrocarbon deposits
- Nitrite- and amine-free
- Contains an inhibitor package for multimetal protection

- Requires mechanical action to be effective
- Leaves no residual film and will not affect paint adhesion qualities
- Prevents flash rust
- Safe to use on glass and most plastics
- Non-foaming
- VpCI-418 LM is silicate free, giving the maximum surface cleanliness after cleaning

### EFFECTIVE USES

- Machinery, engine blocks, or forgings coated with grease or oil deposits
- Plate, sheet metal and metal castings covered with oily films prior to painting or pickling
- Metal parts contaminated with stamping, drawing or buffing compounds
- Pressure washing

### APPLICATION

VpCI-418L/418LM can be applied using power washers and sprayers.

Mix VpCI-418L/418LM into water until fully dissolved. Take pH and refractometer measurements to establish benchmark readings.

### RECOMMENDED DILUTIONS

#### Light cleaning:

Use 3-5% (by weight) VpCI-418 Liquid or VpCI-418 LM in water.

#### Normal cleaning:

For machinery, rail cars, offshore equipment and tanks contaminated with medium deposits, use 5-7% (by weight) VpCI-418 Liquid or VpCI-418 LM in water.

#### Heavy-duty cleaning:

For drilling mud, grease, crude, bilges, concrete surfaces and structures, use 7-10% (by weight) VpCI-418L/418LM in water.



**Steam cleaning:**

Use 3-5% by weight VpCI-418L/418LM in water.

**Temperature range:**

VpCI-418L/418LM are recommended for use in temperatures ranging from 95°-160°F (35°-71°C).

**PROPERTIES**

**VpCI-418 LM**

Appearance	Yellow to amber clear liquid
pH	10.1-10.6 (1% aqueous)
Non-volatile Content	8-10%
Density	8.6-8.7 lb/gal (1.03-1.04 kg/l)


**VpCI-418 Liquid**

Appearance	Slight hazy yellow liquid
pH	11-12 (1% aqueous)
Non-volatile Content	8-11%
Density	8.9-9.0 lb/gal (1.07-1.08 kg/l)

**PACKAGING**

VpCI-418 LM and VpCI-418 Liquid is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk.

**Figure 1. The refractometry readings for VpCI-418 dilutions.**



\*Multiply Refractometer reading by Refractometer index to determine concentration.

**FOR INDUSTRIAL USE ONLY**

**KEEP OUT OF REACH OF CHILDREN**

**KEEP CONTAINER TIGHTLY CLOSED**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

**LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com  
Internet <http://www.cortecvci.com>