



CORROSION INHIBITING VpCI™ POWDERS

Cooling Loop Gator® Patent Pending VpCI™ Tower Lay-up



PRODUCT DESCRIPTION

Cortec's Cooling Loop Gator® is a Vapor phase Corrosion Inhibitor (VpCI™) powder packaged in polyvinyl-alcohol (PVA) water-soluble packages. Developed for seasonal, short or long term lay-up, Cooling Loop Gator® protects enclosed spaces for up to 12 months. Once the bag and powder dissolve, the VpCI™s adsorb on all metal surfaces - reaching even recessed areas and interior cavities. The VpCI™s form a strong molecular layer on the metal that protects in the liquid phase and vapor phase.

FEATURES

- Provides excellent corrosion protection during lay-up period
- Can be used as a corrosion inhibitor additive in the majority of water treatment programs
- Provides multimetal protection, including galvanized steel and yellow metals (copper, brass)
- Protects inaccessible and recessed surfaces
- Does not need to be removed prior to start up

- Eliminates environmental hazard and disposal problems
- Safe and easy to handle
- Fully biodegradable, non-toxic and non-irritating
- Effective for wet lay-up and flushing applications
- Reduces chemical consumption and cost upon start up
- Easy to apply
- Increased worker productivity and safety
- Nitrite-, phosphate-, and chromate-free
- Compatible with the majority of commercially available biocides and antiscalants

METHOD OF APPLICATION

One Gator treats up to 250 gallons (0.95 m³) water. Remove and discard outer barrier bag. Add the water-soluble bags directly into cooling water. Recirculate treated water for about 10-12 hours to obtain good protective layer before shutdown. Either drain the water out (flushing lay-up) or leave treated water in cooling tower. After application, all internal surfaces should be covered or closed and valves shut off.

COMPATIBILITY

Cooling Loop Gator® is effective in the:

- Presence of non-oxidizing biocides
- Presence of oxidizing biocides*

Cooling Loop Gator is compatible with most materials of construction in cooling towers (e.g. rubbers, polymers, etc.).

*Keep free halogen concentration less than 4 ppm. In using a high concentration level of oxidizing biocides, consult Cortec about dosages.



DIMENSION

Bag 10" x 14" (25 cm x 35 cm)

PHYSICAL PROPERTIES OF POWDER

Appearance White to off-white powder
pH 10-12 (1% aqueous)

EPA/600/4-90/027F

Meets EPA requirements for discharge in freshwater in used concentration.

48-hour Static *D. pulex* and *P. Promelas* Toxicity Test (fresh water):

EE#	Appendix	Sample ID	NOEC/LOEC, ppm	
			<i>D. pulex</i>	<i>P. Promelas</i>
E-17766-01	A	Cooling Loop Gator®	10,000/>10,000	10,000/>10,000

PACKAGING AND STORAGE

Cooling Loop Gator® is available in 4 x 2.2 lb (4 x 1 kg) bags per box. Store in sealed container in a dry and cool warehouse. Do not store in conditions above 150°F (66°C).

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.CortecVpCI.com>

Distributed by:

printed on recycled paper 10% post consumer

Revised 10/22/02. ©Cortec Corporation 2002. All rights reserved. Supersedes: 9/20/00. Cortec®, Cooling Loop Gator®, and VpCI™ are trademarks of Cortec Corporation.



Certificate No.70781

Certificate No.81867