

## **Product Description**

Eco-Tie<sup>™</sup> is a high-strength, completely biodegradable/compostable (per ASTM 6400 standards) alternative to twine and metallic/plastic ties used in agricultural and industrial markets. Unlike metallic and plastic ties, Eco-Tie<sup>™</sup> will biodegrade rapidly when exposed to other organic materials, but will retain strength while in use. This unique and proprietary technology was designed specifically for vineyards where the grape plants are tied to metal wire and fences during their growing cycle. By using Eco-Tie<sup>™</sup>, wine producers are able to further minimize the environmental impact of their production.

### **Technical Description**

Eco-Tie<sup>™</sup> is a proprietary blend of polyesters, which originate from alcohols and acids. The polyesters in Eco-Tie<sup>™</sup> are specifically engineered to be directly consumed by microorganisms when they are placed in direct contact with soil or compost. When Eco-Tie<sup>™</sup> is in use, it typically is not in direct contact, therefore biodegradation will only begin when it is disposed or discarded.

## **Construction and Availability**

Standard Eco-Tie <sup>™</sup> is supplied on spools and is a single strand of compostable plastic. Custom runs are possible with up to 3prong strands of any length. Elasticity and strength can also be modified to meet various customer demands.

# ECO-TIE<sup>TM</sup>

### HIGH PERFORMANCE, BIODEGRADABLE TIE

### **Biodegradability**

Eco-Tie<sup>™</sup> is based on compostable materials that are certified for commercial compostability by BPI (International Biodegradable Products Institute) and Din Certco (IBAW mark) per ASTM D 6400, offering consumers confidence that Eco-Tie<sup>™</sup> will biodegrade rapidly and safely when disposed of properly. When Eco-Tie<sup>™</sup> is disposed of in commercial composting environments, it is directly consumed by microorganisms and converted naturally into carbon dioxide and water, typically within 45-60 days. When disposed of in soil, the rate of biodegradation rate is dependent on the soil content and conditions such as temperature and moisture, but typically occurs in 60-365 days.

# **Application & Use**

Eco-Tie<sup>™</sup> is specifically designed to meet the demands (strength, usability, convenience) of agricultural companies such as vineyards and nurseries. The most common application is to use Eco-Tie<sup>™</sup> to support young plants and samplings during the initial growth periods of several months to several years. By using Eco-Tie<sup>™</sup> to secure young plants to stakes, fences or similar structures, the stems are less susceptible to environmental damage. Additionally, Eco-Tie<sup>™</sup> can be effectively utilized to direct growth patterns for all types of plants or as an alternative tie/closure mechanism for shipments and packaging of all sorts.

## Shelf Life & Useful Life

Until exposed to microorganisms or similar environments, Eco-Tie<sup>™</sup> will remain stable. When in use, Eco-Tie<sup>™</sup> will remain strong and usable until exposed to microorganisms, excessive heat, or excessive UV exposure. Moisture and heat alone will not degrade Eco-Tie<sup>™</sup> under most conditions. However since moisture and heat allow microorganisms to become more active, these factors can indirectly reduce the shelf life and useful life.



FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN NOT FOR INTERNAL CONSUMPTION CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

### LIMITEDWARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec <sup>\*</sup> products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement product shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document

representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.cortecvci.com

printed on recycled paper 10% post consumer Revised 8/2/05. Cortec Corporation 2005. All rights reserved. Supersedes: None Distributed by: