

# Gator S

## Cleaner/Degreaser, VpCl<sup>®</sup>, and Bio-growth Controller



### DESCRIPTION

Gator S is a heavy-duty non-foaming alkaline cleaner/degreaser for cleaning industrial, oil field, commercial, and marine equipment. This product contains VpCl additive to prevent corrosion on the parts and a special agent to protect the working solution from bacteria growth.

Gator S is non-flammable, nitrite-free, non-toxic, and does not present disposal problems associated with most phosphate cleaners.

Gator S offers a very convenient delivery system-it is packaged in a water-soluble polyvinyl alcohol bag (PVA) for safe handling and easy measurements. Simply place the bag into the wash system and allow the bag and powder to dissolve.

### FEATURES

- Heavy-duty alkaline cleaner and degreaser with unique cleaning action for removing hydrocarbon deposits
- Nitrite- and amine-free
- Contains an inhibitor package for multimetal protection
- Has an additive to control biogrowth in the system
- Requires mechanical action to be effective
- Leaves no residual film and will not affect paint adhesion qualities
- Prevents flash rust
- Safe to use on glass and most plastics
- Non-foaming
- Available in a convenient delivery system packaged in a water-soluble polyvinyl alcohol bag

### EFFECTIVE USES

- Machinery, engine blocks, or forgings coated with grease or oil deposits
- Plate, sheet metal, and metal castings covered with oily films prior to painting or pickling
- Metal parts contaminated with stamping, drawing, or buffing compounds
- Pressure washing

### APPLICATION

Simply place product into the wash system and allow to dissolve.

## USAGE

Light cleaning:

1 pound of powder or 1 water-soluble bag per 5 gal in water.

Heavy-duty cleaning:

2-3 pounds of powder or 2-3 water-soluble bags per 5 gal in water.

## PROPERTIES OF POWDER

Appearance	Off-white powder
pH	11.8-12.8 (1% aqueous)
Non-volatile Content	97-100%

## PACKAGING

Gator S is available in 5 lb (2.3 kg) boxes, 50 lb (23 kg) drums, 100 lb (45 kg) drums; or 5 water-soluble bags per carton, each bag contains 1 lb (0.45 kg) of material.

## STORAGE AND HANDLING

Keep away from moisture.

Temperature range:

Gator S is recommended for use in temperatures ranging from 95°-160°F (35°-71°C).

## FOR INDUSTRIAL USE ONLY

**KEEP OUT OF REACH OF CHILDREN**

**NOT FOR INTERNAL CONSUMPTION**

**CONSULT SAFETY DATA SHEET FOR MORE**

**INFORMATION**

## LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 11/1/13. ©Cortec Corporation 2007-2013. All rights reserved. Supersedes: 3/10/09.  
VpCI® is a trademark of Cortec Corporation. 2013, ©Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.