



## VpCI™ ADDITIVES FOR COATINGS, FLUIDS, ADHESIVES AND PLASTICS

# M-151

### PRODUCT DESCRIPTION

Cortec M-151 is a Vapor phase Corrosion Inhibitor Ink Additive that will produce a multimetal VpCI coating on paper or film backing material. This additive is usually mixed with compatible ink solutions at a 1:1 ratio and applied at a coating weight that is easily reached on most printing equipment. The resultant layer will produce a thin, non-penetrating coating on paper and film. This product will have an exceptional shelf-life and has solved corrosion problems associated with paper and film in the past.

The M-151 can be used to coat Post Consumer Recycle (PCR) products. A pinhole free coating needs to be applied and can be obtained by putting multiple thin layers down in a controlled manner. The resultant film has the typical VpCI protection properties of other Cortec products. The new constructions produced with this coating are expected to be useful to many companies that now rely on heavy oils, greases and/or additional paper or film wrappings to provide corrosion protection. This new coating additive provides multimetal protection to metals including steel, galvanized steel, aluminum, copper, brass, silver solder, etc.

### TYPICAL APPLICATION

Cortec M-151 is a solvent mixture that is compatible with a number of ink resins. It is mixed in a 1:1 ratio with an ink resin formulation and applied directly to the paper or film backing using gravure and/or flexographic printing machines. Drying is achieved by use of a warm air oven or with IR bulbs. The unused mixed coating solution should be properly disposed of after 30 days.

A minimum dry coating weight of 2-3 lbs per ream (3.27-4.90 g/m<sup>2</sup>) or 7-9 lbs per ream wet (11.43-14.78 g/m<sup>2</sup>) is recommended to achieve maximum shelf life. When additional procedures such as corrugating, laminating or further coating is required, a heavier coating weight is suggested. Also, in cases where a highly reactive metal is packaged for long term storage in warm humid climates, a heavier coating weight is recommended.

The solvent blend used in the M-151 is typically used for solvent based printing inks. A trial run using clear or pigmented resin solutions should be attempted before a full run is planned. In cases where there is a need for faster drying or wetting of film or paper surfaces, special solvent mixtures can be obtained as a custom product.

### PHYSICAL PROPERTIES

Solids content Weight (%)	10-15
Solvent composition	75% Ethanol
Density	7.2-7.4 lb/gal (0.87-0.89 kg/l)
pH	7.8-8.0

### PACKAGING AND STORAGE

M-151 is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes and bulk. M-151 should be sealed before storage. The shelf life is up to 24 months.



**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION**

#### **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
Internet <http://www.CortecVpCI.com>

printed on recycled paper  10% post consumer  
Revised 5/1/06. Cortec Corporation 1994-2006. All rights reserved. Supersedes: 3/26/96.  
© 1994-2006. Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.