

# **MCI®-2060**

#### DESCRIPTION

MCI-2060 is a cleaner and degreaser that contains Migratory Corrosion Inhibitors<sup>®</sup> (MCIs). It effectively cleans caked on grease, dirt, oil, and mud on concrete driveways, garage floors, walkways and curbs; making them look like new.

#### WHERE TO USE

- Removal of oils, greases, dirt from all concrete and ceramic surfaces
- Cleaning/degreasing of sealed or painted concrete surfaces
- Can be used to neutralize one of Cortec's VpCl<sup>®</sup> rust removers (VpCl 422, VpCl 423, VpCl 426, etc.)

#### ADVANTAGES

- Good for various oils and greases
- Will not damage sealed or painted surfaces
- Non-flammable
- Remains active even if left to dry
- Non-toxic and biodegradable
- May be used at room temperature to reduce energy consumption
- Viscous liquid will cling to ceilings and vertical surfaces in a ready-to-use formulation
- Replaces caustic-based and strong acid-based concrete cleaners
- No special protective equipment needed for application
- Provides flash rust corrosion protection to metals it comes in contact with
- Adjacent areas do not need special protection during application
- Removes cosmoline, transit coatings, and sludge

### **PHYSICAL PROPERTIES**

Appearance Density pH Non-volatile Content Usage Clear light yellow liquid 8.6-8.7 lb/gal (1.03-1.04 kg/l) 10.9-11.4 (Neat) 18-25% 1% up to concentrate

#### CONSIDERATIONS

MCI-2060 it contains is not designed for long term corrosion protection or to penetrate/migrate distances into concrete. MCI-2060 can only protect reinforcing metal when applied to bare concrete or directly onto the metal.

## APPLICATION

#### For cleaning:

- 1. Brush, roll, or spray MCI-2060 onto a concrete surface.
- 2. Use a deck brush to agitate the surface.
- Allow MCI-2060 time to clean. Depending on how soiled the surface is, it may take several minutes to one hour.
- Rinse the loosened grime from the concrete surface using water. If possible, use a pressure washer. Floors may also be flooded with water and the debris brushed away or wet-vacuumed up.

#### PACKAGING AND STORAGE

MCI-2060 is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. Store between 32°F (0°C) and 120°F (49°C).



FOR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED NOT FOR INTERNAL CONSUMPTION CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

#### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com Internet http://www.cortecvci.com



Distributed by: