



# VpCI®-322 D



## PRODUCT DESCRIPTION

VpCI®-322D is a ready-to-use version of VpCI®-322, diluted 1:4 with standard hydraulic oil, for inhibiting corrosion in tanks, gearboxes, and hydraulic systems. Oil-soluble corrosion inhibitors in VpCI®-322D form a tenacious film on the metal surface, providing excellent contact corrosion protection. VpCI®-322D also releases vapor phase corrosion inhibitors into the air space above the oil. These inhibitor molecules attach to metal surfaces providing vapor phase corrosion protection above the fluid.

## FEATURES

- Provides corrosion protection for ferrous and yellow metals
- Does not contain hazardous barium, chromates, nitrites, or phosphate inhibitors
- Ready-to-use for preservation – no dilution or mixing required
- Can be used in hydraulic applications
- Can be surface applied by spray or brush

## TYPICAL APPLICATIONS

VpCI®-322D is a pre-diluted version of VpCI®-322. Tanks, gearboxes, and hydraulic systems should be filled with VpCI®-322D to be preserved for up to 24 months. VpCI®-322D can be spray or brush applied to metal surfaces as a thin, oily film for corrosion protection.

## METALS PROTECTED

- Carbon Steel
- Stainless Steel
- Galvanized Steel
- Cast Iron
- Copper
- Brass
- Aluminum

## TYPICAL PROPERTIES

Appearance	Amber Color
Specific Gravity	0.9
Viscosity (40 °C)	71 cSt

\*Properties listed above are typical values obtained through normal production and do not constitute a specification.

## PACKAGING AND STORAGE

VpCI®-322D is packaged in 200 liter drums and 1000 liter totes. The product should be sealed before storage. The shelf life of VpCI®-322D is up to 24 months.

\*Only available in Europe



**FOR INDUSTRIAL USE ONLY**  
**KEEP OUT OF REACH OF CHILDREN**  
**KEEP CONTAINER TIGHTLY CLOSED**  
**NOT FOR INTERNAL CONSUMPTION**  
**CONSULT SAFETY DATA SHEET FOR MORE**  
**INFORMATION**

#### **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.  
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 03/01/18. Supersedes: 02/22/18. ©Cortec Corporation 2002-2018 of Cortec Corporation.  
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2018, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.