

CORROSION INHIBITING VpCI® POWDERS

VpCI® Powder Applicator



PRODUCT DESCRIPTION

The VpCI® Powder Applicator has been engineered specifically for fogging of VpCI® powders (VpCI®-307, VpCI®-309, and VpCI®-609). The unit is power-driven by compressed air and can be used in all Ex Zones. It is possible to adjust both the amount of air and powder to achieve the best fogging result for different applications.

FEATURES

- Lightweight for shipping
- Easy to move around
- Hose can be disconnected from unit
- Air inlet at the bottom to make unit stable during work
- 1 1/4 in (3.1 cm) hose for transportation of powder gives high amount of powder for large applications
- Big opening for filling of powder (9.8 in [25 cm] diameter loading nozzle)
- Possible to regulate the flow of powder and amount of air

TECHNICAL SPECIFICATIONS

Maximum air pressure inlet:	145 psi (10 bar g)
Maximum air pressure outlet:	145 psi (10 bar g)
Maximum powder in vessel:	33 lbs (15 kg)
Length of hose:	16.4 ft (5 m)

- Valve for adjusting the air circulation in the vessel
- Air regulator for adjusting inlet air
- Pressure Gauge, range 0-145 psi (0-10 bar)

TECHNICAL DESCRIPTION

Size:

L:	21.65 in (55 cm)
W:	16.93 in (43 cm)
H:	35.43 in (90 cm)

Weight: 33 lbs (15 kg)

The unit has wheels for transportation.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR
MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvc.com
 Internet <http://www.cortecvc.com>

printed on recycled paper 10% post consumer

Revised 3/3/03. Cortec Corporation 2003. All rights reserved. Supersedes: none
 VpCI® is a trademark of Cortec Corporation.



Certificate No.70781

Certificate No.81857