

Editorial Contact: Shannon Garrow
Cortec® Advertising Agency: (651) 429-1100 Ext. 128

sgarrow@cortecvci.com

Company Contact: Cliff Cracauer
Cortec® Corporation: (651) 429-1100 Ext. 181

Cliff@cortecvci.com

Technical Contact: Angel Green
Cortec® Corporation: (651) 429-1100 Ext. 146

agreen@cortecvci.com



Attention: Editor

September 5, 2008

NEWS RELEASE

Cortec® primer provides long-term protection in a corrosive atmosphere.

Cortec's VpCI™-395 is a waterborne epoxy primer that has superior adhesion while providing salt spray, immersion, and long-term corrosion protection to steel. The water-based formulation complies with environmental regulations governing solvents and VOC limits without compromising performance, aesthetics, or durability.



VpCI™-395 may be applied by spray or brush; a dry film thickness of 1.5-3 dry mils (37.5-75 microns) is recommended. The coating dries to the touch in about 20-30 minutes and it takes approximately one week for the coating to fully cure. A topcoat can be applied as early as 30 minutes after the primer is applied, depending on the type of topcoat and drying conditions. Clean up is easy using soap and water.

Photo: Please contact Cortec® Advertising for a High-resolution photo. sgarrow@cortecvci.com

Company Description: Cortec® Corporation is a pioneer of environmentally friendly, corrosion protection Vapor phase Corrosion Inhibitors (VpCI™) & Migratory Corrosion Inhibitors (MCI®) Technologies for the Packaging, Metalworking, Construction, Electronics, Water Treatment, Oil & Gas, and other industries. Headquartered in St. Paul, Minnesota, Cortec® manufactures over 400 products distributed worldwide. ISO 9001 & ISO 14001:2004 Certified.

Cortec Website: <http://cortecadvertising.com> Phone: 1-800-426-7832 FAX: (651) 429-1122

— End —