

HIGH PERFORMANCE VpCI® PACKAGING

CorShield® Fabric, Patented



PRODUCT DESCRIPTION

CorShield, is a multiple-layered protective fabric with a non-woven, soft inside layer. CorShield Fabric is made from low-density polyethylene tapes, a high-density coating, and a non-woven laminate on the inside. CorShield Fabric protects valuable items from corrosion and mechanical damage (i.e. scratching) during storage and shipment. CorShield Fabric offers complete protection to valuable items from machinery to vehicles. Reusable and recyclable, CorShield Fabric can be sewn to custom sizes and covers.

CorShield Fabric is the solution for corrosion packaging problems. Incorporating Cortec's proven Vapor phase Corrosion Inhibitors, this fabric is effective for preventing corrosion on many types of metals.

CorShield Fabric provides outdoor long-term protection against UV exposure (up to 5 years in sunny and hot climates).

APPLICATIONS

- Export and domestic packaging of expensive equipment
- Cars, vans, boats, trucks, motorcycles, and snowmobiles
- Military equipment
- Steel coils
- Heavy equipment and flat stack covers
- Pallet shrouds
- Precision scientific equipment

METALS PROTECTED

- Carbon steel
- Galvanized steel
- Stainless steel
- Copper and alloys
- Aluminum and Aluminum alloys
- Silver
- Solder

FEATURES

- Strength and tear resistance
- Available with zippers, velcro, and elastic closures for a custom fit and reusability
- 100% recyclable, non-toxic, and environmentally friendly

PHYSICAL PROPERTIES

Construction (ASTM D-3775)

48 tapes/10 cm warp (12 per inch)

90 tapes/10 cm weft (10 per inch)

Unit Weight (ASTM D-3775)

6.5 oz/yd² (220 g/m²)

Tensile Grab Strength (ASTM D-1862-64)

950 newtons warp

800 newtons weft

Tear Strength* (tongue) (ASTM D-2261-71)

280 newtons warp

280 newtons weft

Coating Thickness (ASTM D-1777 MOD)

38 mm (side 1) (1.5 mils)

25 mm (side 2) (1 mil)

Width

Up to 2050 mm (78")

*Includes force to shift tapes. Tear may be crosswise to direction of force.



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technology

PACKAGING AND STORAGE

CorShield Fabric is available in rolls or can be custom sewn to precisely fit a particular application. The product should be stored indoors, sealed in the original packaging in temperatures not exceeding 85°F(29°C). When stored in these conditions the shelf life is up to 24 months.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE

INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Distributed by:



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised: 8/26/13. ©Cortec Corporation 2000-2013. Supersedes: 1/23/13.
Cortec®, CorShield®, are trademarks of Cortec Corporation. © 2013, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.