



VpCI® FORMULATED PRODUCTS FOR PROCESS INDUSTRIES

# Corrosorber® Liquid Hydrogen Sulfide Scavenger



## PRODUCT DESCRIPTION

Corrosorber® Liquid is a concentrated solution of nitrogen based heterocyclic compound. It can be used to scavenge hydrogen sulfide ( $H_2S$ ), mercaptans, sulfides, and sulfur compounds from gas systems or liquid hydrocarbons. Corrosorber® liquid is a quickly reacting product allowing for lower levels of treated  $H_2S$  where contact time is restricted.

## FEATURES

- Fast, effective sulfide removal
- Can be used in gas, crude oil, or water
- Not adversely affected by the presence of carbon dioxide

## APPLICATIONS

Hydrogen Sulfide is a poisonous gas that is deadly at high concentrations and provides serious health threats at moderate concentrations. Operating problems caused by  $H_2S$  can include severe corrosion and fouling, and injection well plugging with iron sulfides.

Corrosorber® Liquid is installed in batch reaction towers or it is injected continuously into gas gathering lines, transmission lines, vapor overheads, or liquid product systems of pipelines. It can be applied in either flowline or bubble tower applications. Typically the bubble tower should be filled to approximately 50% full to prevent the product from being carried downline.

Corrosorber® Liquid can be diluted with water or methanol for ease of application. Water containing reacted product can be reused in the water cycle; including water gathering lines, water tanks, holding pits, vapor overheads, or injected down disposal wells.

## METHOD OF APPLICATION

The amount of Corrosorber® Liquid required depends upon the level of  $H_2S$  in the system and the degree of reduction desired. As a general rule, each gallon of Corrosorber® Liquid will scavenge approximately 3.3 pounds of  $H_2S$  per MMSCF. Typical field blend uses 30% Corrosorber® Liquid with 0-15% methanol in water. Additional methanol can be added to the product to meet specification application needs. This is particularly advantageous in wet gas systems where freezing is a problem.

## TYPICAL PROPERTIES

Appearance	Light yellow liquid
pH	10-12 (neat)
Density	9.1-9.5 lb/gal (1.09-1.14 kg/l)
Pour Point	20 °F (-28 °C)
Solubility	
Fresh Water	Soluble
High TDS Brine	Soluble
Isopropanol	Soluble
Xylene	Insoluble

## PACKAGING AND STORAGE

Corrosorber® Liquid is available in 5 gallon (19 liter) pails and 55 gallon (208 liter) drums.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 3 years



**FOR INDUSTRIAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN  
KEEP CONTAINER TIGHTLY CLOSED  
NOT FOR INTERNAL CONSUMPTION  
CONSULT SAFETY DATA SHEET FOR MORE  
INFORMATION**

#### **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 03/20/19. Supersedes: 02/07/19. ©Cortec Corporation 2002-2019 of Cortec Corporation.  
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2019, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.