



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

EcoClean® Scale and Rust Remover HP

DESCRIPTION

EcoClean® Scale Remover HP is a heavy-duty scale and rust remover. It is one of the safest fast acting products on the market for dissolving calcium carbonate and oxides. Powerful corrosion inhibitors contained in EcoClean® Scale Remover HP protect the treated metals from flash rust.

EcoClean® Scale Remover HP is an acid replacement technology that uses low pH organic salt to replace traditional harsh mineral and organic acids.

PACKAGING & STORAGE

EcoClean® Scale and Rust Remover HP is available in 5 gallon (19 L) pails, 55 gallon (208 L) polyethylene drums, and bulk. It can be stored in high-density polyethylene, polypropylene, or fiberglass containers.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

SURFACE PREPARATION PRODUCTS



FEATURES

- Fast-acting scale and rust remover
- Contains powerful corrosion inhibitors to prevent flash rust
- Excellent safer choice to replace muriatic acid for scale or rust removal
- Classified as a mild skin irritant according to the OECD Principles of GLP (Good Laboratory Practice)
- Phosphate free
- No VOCs
- Low contributor to BOD/COD in effluents
- Classified as non-corrosive to mild steel
- Components approved for use in Green Seal®* and Canadian EcoLogo products
- Components approved by the US EPA as a non-food inert ingredient in biocide applications
- Biodegradable
- Improves flow in water pipes or drainage pipes obstructed by scale
- Improves heat-transfer efficiency on heat-exchanger equipment by creating clean surfaces
- Non-regulated for ground shipments per US DOT; regulated for air and marine transportation

TYPICAL APPLICATION

- Safer scale removal on all water-contacting equipment surfaces including heat-exchangers, chillers, condensers, cooling towers, and pipes
- Safer multi-metal rust removal

METHODS OF APPLICATION

Apply EcoClean® Scale and Rust Remover HP undiluted or diluted (up to 1:3 in water) to the surfaces needing treatment, and allow contact time from 5 minutes up to 1 hour, depending on the amount of scale and corrosion. Light abrasion helps removal of loosened scale or corrosion products and speeds up the remover penetration. Rinsing with a neutralizing cleaner such as VpCI®-416 or VpCI®-414 provides further protection.

EcoClean® Scale and Rust Remover HP

TYPICAL PROPERTIES

Appearance	Clear Yellow to Amber Liquid
Density	9.1-9.3 lbs/gallon (1.09-1.11 kg/L)
pH	<1 (neat)

CONSIDERATIONS

EcoClean® Scale and Rust Remover HP can be reused. Remove any sediments after use and check pH of the solution (pH=<2) before reuse.

- EcoClean® Scale and Rust Remover HP does not damage moisture-cured-aliphatic-urethane painted surfaces, common uncoated glass surfaces, fiberglass, and rubber.
- Immersion produces best results for most substrates.
- Spraying of EcoClean® Scale and Rust Remover HP may produce discoloration on certain metals (brass and some stainless steel appear to be most affected). Test compatibility in an inconspicuous area before use.
- Follow the SDS on handling of the material.

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC
productinfo@cortecvci.com
<http://www.cortecvci.com>



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.