



EcoLine® AL-Corr[™]

DESCRIPTION

A corrosion inhibitor for aluminum agricultural irrigation pipes, EcoLine® AL-Corr[™] is designed to provide protection while the irrigation system is in use, as well as during times of intermittent irrigation water flow. It is formulated with biodegradable materials that are approved for use in personal care products and food preservation.

PACKAGING & STORAGE

EcoLine[®] AL-Corr[™] is available in 5 gallon (19 L) pails, 55 gallon (208 L) drums, liquid totes, and bulk.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

WATER TREATMENT SOLUTIONS



FEATURES

- Readily water-soluble
- Effective at low dosages
- Contains no phosphates or nitrites
- Formulated with renewable raw material
- Formulated with ingredients approved for personal care products and for food packaging materials
- Contains 81% USDA certified biobased content
- Contains a PTSA tracer for concentration monitoring

BENEFITS

- Protects internal surface of aluminum irrigation pipes from corrosion
- Reduces corrosion rate by more than 90% in immersion conditions

APPLICATION

Add to irrigation water at a dose rate of 250–500 ppm.

TYPICAL PROPERTIES

Appearance	Yellow Viscous Liquid
Density	8.3-8.7 lb/gal (0.99-1.04 kg/L)
рН	7-8

TEST RESULTS

ASTM G 31 Immersion (104 °F [40 °C], 5 Weeks)			
Dosage	Corrosion Rate (MPY)	% Protection	Alloy
0 ppm	6.67	NA	AL 3003
250 ppm	0.59	91.18%	AL 3003
0 ppm	6.47	NA	AL 1100
250 ppm	0.06	99.03%	AL 1100

PTSA TRACER DETECTION		
EcoLine [®] AL-Corr™ Concentration	PTSA Contribution	
250 ppm	75 ppb	
500 ppm	180 ppb	

4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC productinfo@cortecvci.com https://www.cortecvci.com https://www.cortecwatertreatment.com







LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec* Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC* CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Revised: 04/18/24. Supersedes: 09/08/21. ©Cortec Corporation 2002-2024 of Cortec® Corporation. All Rights Reserved. Copying and/or manipulation of these materials in any form without the written authorization of Cortec® Corporation is strictly prohibited. 2024, ©Cortec® Corp. ISO accreditation applies to Cortec's processes only.