



VpCI® Heavy Duty Lubricants & Greases

EcoLine® Bio-Based Food Machinery Grease #1 and #2



FEATURES

- Formulated in accordance with U.S. FDA regulation 21 CFR 178.3570, "Lubricants With Incidental Food Contact"
- Listed as part of the USDA BioPreferred® Program
- Operates under a wide range of temperatures
- Contains extreme pressure additives
- Biodegradable
- Not toxic to plants*

BENEFITS

- Provides superior lubricity to moving parts
- Protects ferrous metals from rust
- Protects equipment/gears under heavy shock loads
- Resists water washout

APPLICATION

Apply to food machinery or other equipment wherever NLGI grade 1 or 2 grease is needed.

- Typical applications for Grease #1:
- Low speed bearings
 - Oscillating machinery
 - Other ambient or low temperature applications

- Typical applications for Grease #2:
- Bearings
 - Gears
 - Machine slides

*It is always important to ensure that use and disposal of all materials is in accordance with local guidelines.



PRODUCT DESCRIPTION

EcoLine® Bio-Based Food Machinery Lubricating Grease #1 and #2 are NLGI grade 1 and 2 greases for lubrication of machinery where there is the possibility of incidental contact with food. Made from natural seed oils, EcoLine® Bio-Based Food Machinery Grease #1 and #2 provide superior lubricity to moving metal parts. They show good adhesion to resist water washout and have a wide range of operating temperatures. EcoLine® Bio-Based Food Machinery Lubricating Grease #1 and #2 contain 96% USDA certified biobased content and are qualified products under the mandatory federal purchasing initiative of the USDA BioPreferred® Program. They are ready to meet demanding lubrication applications in the food and beverage processing industries. EcoLine® Bio-Based Food Machinery Lubricating Grease #1 and #2 are registered with the NSF Nonfood Compounds Registration Program as H1 category lubricants for incidental food contact (Reg. #157337 and Reg. #157338, respectively).



TYPICAL PROPERTIES

Oil Characteristics		Typical Values	
		EcoLine® Food Machinery Lubricating Grease #1	EcoLine® Food Machinery Lubricating Grease #2
NLGI Grade		1	2
Appearance		Golden	Golden
Base Oil Viscosity	40 °C (104 °F)	130	130
	100 °C (212 °F)	22	22
	Index	198	198
Dropping Point (ASTM D2265)		265 °C (509 °F)	273 °C (523 °F)
Penetration, 60 strokes (ASTM D-217)		340	280
Four Ball Wear Scar		0.48 mm	0.48 mm
Four Ball Weld Load		200 kg	200 kg
Corrosion (ASTM D-1743)		Pass	Pass

STORAGE AND PACKAGING

Available in 14 ounce (396 g) cartridges (12 per carton), 5 gallon (19 liter) plastic pails, and 55 gallon (208 liter) metal drums.

To avoid separation, store in a cool, dry area at 32-86 °F (0-30 °C). EcoLine® Bio-Based Food Machinery Lubricating Grease #1 and #2 should be stored in a sealed container. Exposure to high temperatures, dust, dirt, or other contaminants can severely deteriorate the quality of the product.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
 BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<https://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 07/25/18. Supersedes: n/a. ©Cortec Corporation 2002-2018 of Cortec Corporation.
 All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2018, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: