



VpCI® METALWORKING PRODUCTS



EcoLine® Drilling Rod Grease



PRODUCT DESCRIPTION

EcoLine® Drilling Rod Grease is a premium quality biobased, biodegradable lubricant for drilling rod applications. It contains extreme pressure additives and graphite for excellent protection where constant drilling vibration creates a high load on drilling rod joints. EcoLine® Drilling Rod Grease is recommended for use in environmentally sensitive areas near waterways.

EcoLine® Drilling Rod Grease is formulated from vegetable oils and aluminum complex based thickener. It offers superior lubricity and reduces friction and wear, with a better coefficient of friction than most petroleum-based grease. EcoLine® Drilling Rod Grease also has a higher flash point than most petroleum greases, increasing safety and allowing use in high temperature applications. It is formulated to be applied to wet surfaces and is available in NLGI grades 1, 2, and 3.

FEATURES

- Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- Meets USDA's proposed biobased product definition for EO 13101
- Excellent for high-pressure, vibrating applications
- High flash point
- Biodegradable
- Not toxic to plants
- Can be applied to wet surfaces

BENEFITS

- Reduces friction and wear
- Improves efficiency of operation
- Provides extreme pressure protection
- Replaces standard non-biodegradable aluminum-thickened grease with biodegradable counterpart

APPLICATION

Apply to drilling rods where lubrication is needed.

TYPICAL PROPERTIES

Physical Properties		Value
Appearance		Golden Brown
Cone Penetration, Unworked	NLGI Grade 1	310-340
	NLGI Grade 2	265-295
	NLGI Grade 3	220-250
Four Ball Wear Scar (mm)		0.55
Four Ball Weld Load (kg)		500
Dropping Point		390°F (199°C)
Oil Separation		<5%
Base Oil Viscosity	104°F (40°C)	185 cSt
	212°F (100°C)	28 cSt
Base Oil Viscosity Index		190
Base Oil Flash Point		619 °F (326°C)
Base Oil Biodegradability (OECD 301)		Pass
Base Oil Aquatic Toxicity (OECD 202)		Non-toxic
Base Oil Plant Toxicity (OECD 208)		Pass



STORAGE AND PACKAGING

Available in 14 ounce (396 g) cartridges (12 per carton), 5 gallon (19 liter) pails, and 55 gallon (208 liter) drums.

To avoid separation, store in a cool, dry area at 32-86°F (0-30°C). EcoLine® Drilling Rod Grease should be stored in a sealed container. Exposure to high temperatures, dust, dirt, or other contaminants can severely deteriorate the quality of the product.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 04/18/18. Supercedes: N/A. ©Cortec Corporation 2002-2017 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2017, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: