



## VpCI® Heavy Duty Lubricants & Greases

# EcoLine® Fifth Wheel Grease



### APPLICATION

Apply to metal contact areas where NLGI grade 2 grease is needed.

- Semi-truck fifth wheel plates
- Trailer hitches and other mechanical joints
- Any other sliding or rolling metal-to-metal contact area

### TYPICAL PROPERTIES

Physical Property	Typical Values
Appearance	Gray/Black
NLGI Grade	2
Cone Penetration, Worked (60x)	265-295
Four Ball Wear Scar (mm)	0.52
Four Ball Weld Load (kg)	400
Dropping Point	338 °F (170 °C)
Oil Separation	<5%
Base Oil Viscosity at 104 °F (40 °C)	51 cSt
Base Oil Viscosity at 212 °F (100 °C)	10.5 cSt
Base Oil Viscosity Index	202
Base Oil Flash Point	619 °F (326 °C)
Base Oil Biodegradability (OECD 301)	Pass
Base Oil Aquatic Toxicity (OECD 202)	Non-toxic

### PRODUCT DESCRIPTION

EcoLine® Fifth Wheel Grease is premium quality biodegradable, multipurpose grease formulated from vegetable oils and a lithium-based thickener. Its superior lubricity promotes longer equipment life by reducing friction and wear. It shows good adhesion to resist water washout and has a wide range of operating temperatures. Advanced extreme pressure additives provide excellent protection.

EcoLine® Fifth Wheel Grease is recommended for use in fifth wheel plates of semi-trucks. It also serves as a biobased, biodegradable replacement for petroleum-based all-purpose greases used in sliding or rolling metal-to-metal contact areas.

### FEATURES

- Contains advanced extreme pressure additives
- Operates under a wide range of temperatures
- Biodegradable
- Not toxic to plants
- Meets EPA's Environmental Preferable Purchasing (EPP) criteria
- Meets USDA's proposed biobased product definition for EO 13101

### BENEFITS

- Extends equipment life by reducing friction and wear
- Increases safety due to higher flash point than petroleum greases
- Biobased, biodegradable replacement for standard greases
- Resists water washout

### STORAGE AND PACKAGING

This product is available in 14 ounce (396 g) cartridges (12 per carton), 5 gallon (19 liter) pails, and 55 gallon (208 liter) drums. To avoid separation, store in a cool, dry area at 32-86 °F (0-30 °C). EcoLine® Fifth Wheel Grease should be stored in a sealed container. Exposure to high temperatures, dust, dirt, or other contaminants can cause severe deterioration of the quality of the product.

**FOR INDUSTRIAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN  
KEEP CONTAINER TIGHTLY CLOSED  
NOT FOR INTERNAL CONSUMPTION  
CONSULT SAFETY DATA SHEET FOR MORE  
INFORMATION**

#### **LIMITED WARRANTY**

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.  
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC, E-mail [info@cortecvci.com](mailto:info@cortecvci.com)  
<https://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 07/23/18. Supersedes: 07/16/18. ©Cortec Corporation 2002-2018 of Cortec Corporation.  
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2018, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.