

ElectriCorr® VpCI®-239 Multi-Metal Cleaner/Protector

DESCRIPTION

ElecriCorr® VpCl®-239 is a multifunctional outdoor cleaner/corrosion protector. It removes oils, grime, wax, and other contaminates with ease, and provides corrosion protection to the treated surface at the same time. ElecriCorr® VpCI[®]-239 forms a very thin film against aggressive conditions including industrial, marine, and tropical regions. The vapor phase inhibitors continuously sublimate to protect difficultto- access areas. ElecriCorr® VpCI[®]-239 can be safely used with most plastics, elastomers, and other non-metallics. Parts and equipment treated with ElecriCorr[®] VpCl[®]-239 and packaged properly afterwards are ready to be deployed at moments notice.

ElecriCorr[®] VpCl[®]-239 is free of CFCs and 1,1,1-Trichlorethane. Provides instant corrosion protection.

UFI: 3A20-H08X-K003-H2KY

PACKAGING & STORAGE

ElecriCorr[®] VpCl[®]-239 is available in 9.45 oz. (267.75 grams) aerosol spray (6 cans per carton), 5 gallon (19 L) pails, 55 gallon (208 L) drums, liquid totes, and bulk

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

VpCI® EMITTING SYSTEMS & ELECTRONIC PRODUCTS



FEATURES

- Excellent outdoor protection
- Can be applied indoors
- · Fast-drying, nonsticky corrosion inhibiting film
- Effective cleaner for grime, oil, wax, and other contaminates
- Instant corrosion protection to ferrous and non-ferrous metals
- Minimized field service
- Increased corrosion protection at a lower cost than conventional rust preventives
- CFC and 1,1,1-Trichlorethane free
- Vapor phase protection in difficult to reach areas
- Moisture-displacing and penetrating film characteristics

TYPICAL APPLICATIONS

- Preservation of cleaned surfaces, parts, and equipment
- De-watering after aqueous cleaning
- Protection between processing steps
- Preservation of pumps
- Preservation of electric motors
- Can be used in contact with engineering plastics, elastomers, and other non-metallics
- Outdoor generators and junction boxes
- Outdoor and indoor electrical outlets

APPLICATION

Spray a very light mist over the area needing protection. Dry time is approximately 1-2 hours at 70 °F (21 °C)and 50% relative humidity.

Note: Application of a heavy mist will result in a heavy film that sags and remains wet.

Shelf life: 3 years

STANDARD TEST METHODS

ASTM D-1748 Humidity Cabinet 300+ Hours

4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC info@cortecvci.com http://www.cortecvci.com





LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec* Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Revised: 03/02/21. Supersedes: 07/13/17. ©Cortec Corporation 2021 of Cortec® Corporation. All Rights Reserved. Copying and/or manipulation of these materials in any form without the written authorization of Cortec® Corporation is strictly prohibited. 2021, ©Cortec® Corp. ISO accreditation applies to Cortec's processes only.