



CORROSION INHIBITING ADDITIVES

M-95



PRODUCT DESCRIPTION

M-95 is a very low foaming, water soluble corrosion inhibitor concentrate.

It provides corrosion protection for steel, copper, brass, magnesium, aluminum, bronze, galvanized steel, and other ferrous and non-ferrous metals and their alloys. M-95 prevents corrosion in both phases: contact and vapor.

FEATURES

- Stable in aqueous systems at pH of 6 or above
- Virtually non-foaming
- Effective at low use levels (0.25-1.0%)
- As a process additive, recommended at 5-10 ppm
- Soluble in water, glycols, and alcohols; insoluble in hydrocarbon-based solvents; dispersible in oils
- Non-phenolic
- Not based on triazole compounds
- Hard water stable
- Nitrite and phosphate free
- Biodegradable
- Non-hazardous, environmentally friendly
- In compliance with HOCNF (Harmonized Offshore Chemical Notification Format) environmental requirements
- UFI: 5GU4-52RN-EU1M-GHOT

TYPICAL PROPERTIES

Appearance	Clear amber liquid
pH	8-9 (Neat)
Density	8.4-8.7 lb/gal (1.01-1.02 kg/l)
Non-volatile (weight)	63-78%

STANDARD TEST REFERENCE CHART

ASTM G-31	Immersion Corrosion Test
ASTM D4627	Cast Iron Chip
NACE TM-0208-2008	Vapor Inhibiting Ability Biodegradability (OECD Method 301D)

APPLICATION

- Protection of distillation towers
- Petroleum processing
- Synthetic coolants and cutting fluids
- Industrial cooling towers
- Water based lubricants
- Aerosol formulations
- Paint additives
- Treating baths for copper and copper alloys
- Alkaline metal cleaners
- Radiator fluid additive
- Anti-freeze ethylene glycol/water based formulations

STORAGE AND PACKAGING

M-95 is packaged in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years



**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Distributed by:



4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 06/07/16. Supersedes: 03/28/16. ©Cortec Corporation 2002-2016 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2016, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.