



VpCI® ADDITIVES FOR WATER TREATMENT



S-10 F Boiler Additive



PRODUCT DESCRIPTION

Non-toxic “green” filming corrosion inhibitor for boiler condensate. Effective against corrosion caused by carbon dioxide and oxygen. Excellent replacement for film forming amines (steam line).

Resistant to oxidation and has high salt tolerance. Outstanding film for persistency and stability in a wide temperature range.

Compatible with the majority of ingredients used in boiler and condensate line treatment programs.

FEATURES

- Economical
- Compatible with most products used in water treatment
- High efficiency against corrosion caused by carbon dioxide and oxygen
- Does not hydrolyze during the application
- Can be used as continuous and/or batch treatment

TYPICAL APPLICATION

Appearance	Slightly yellow liquid
pH	7-8 (Neat)
Non-volatile Content	25-35%
Density	8.5-8.7 lb/gal (1.02-1.04 kg/l)

DOSAGE

S-10 F should be added directly to condensate lines as a continuous or batch treatment. As a continuous treatment, S-10 F should be added at a concentration level of 10-30 ppm (depending on oxygen and CO₂ content).

As a batch treatment, a concentration of up to 500 ppm should be maintained. The duration of cycles depends on the condition of the condensate line.

TOXICITY INFORMATION

Cortec® S-10 F, additive for steam condensates, contains only FDA approved ingredients which have the following approvals:

FDA# 21 CFR - 175.105
 FDA# 21 CFR - 178.3130
 FDA# 21 CFR - 177.1200

Oral Toxicity:

Product	LD ₅₀ , mg/kg	Remarks
S-10 F	2175, 5000	Mice, rats

PACKAGING AND STORAGE

S-10 F is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. The shelf life is up to 24 months.



**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.
BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 03/24/16. Supersedes: 01/05/16. ©Cortec Corporation 2002-2013 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2013, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: