



VpCI®-330

DESCRIPTION

VpCI®-330 is a clear, ready-to-use low-viscosity rust preventative that provides excellent protection for metals in indoor and outdoor sheltered conditions.

VpCI®-330 leaves a thin, transparent film on protected products and components, which is ideal for metal parts that require an almost invisible coat of oil for further processing and/or shipment, including gears, spindles, coils, or any other component requiring protection but for which subsequent oil removal is either infeasible or not desirable.

FEATURES

- Provides universal corrosion protection to ferrous metals
- Compatible with yellow metals
- Performs effectively even under adverse conditions, including 100% relative humidity and in the presence of corrosive species, such as chlorides
- Non-flammable
- Homogenous
- Contains no chromates, nitrites, phosphates, secondary amines, or OSHA designated hazardous components
- Easily sprayed using handheld trigger spray bottle or other common spray equipment

APPLICATION

VpCI®-330 can be sprayed, dipped, rolled, or brushed onto metal surfaces requiring protection from corrosion. A handheld trigger spray bottle is ideal for easy application.

TYPICAL PROPERTIES*

Appearance	Clear amber liquid
Film type	Transparent oil film
Flash point	>266°F (>130°C)
Viscosity	29 cSt @ 104°F (40°C)

* Typical values represent average laboratory values and are intended as guides only, not as lot specifications.

PACKAGING & STORAGE

VpCI®-330 is available in 5 gallon (19 L) pails, 55 gallon (208 L) drums, 275 gallon (1,045 L) totes, and in bulk. To ensure best product performance, keep sealed in original packaging, indoors, and out of direct sunlight at 40–100° F (4–38° C).

Shelf life: 2 years

STANDARD TEST METHODS

Test Method	Description	Results
ASTM D1748	Humidity Chamber	>600 hrs
ASTM B117	Salt Spray	>26 hrs
ASTM D130	Copper Strip Test	1a

4119 White Bear Parkway, St. Paul, MN 55110
Phone (651) 429-1100
Toll Free (800) 4-CORTEC
productinfo@cortecvci.com
<https://www.cortecvci.com>



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight changes for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.