

VpCI®-330

DESCRIPTION

VpCI®-330 is a clear, ready-to-use low-viscosity rust preventative. It provides excellent protection to metals in indoor and outdoor sheltered conditions. The product leaves a thin, transparent film, great for metal parts that require an almost invisible coat of oil for further processing and/or shipment (e.g., gears, spindles, coils, or any other metal part that should be protected but for which subsequent oil removal is not feasible or desirable).

PACKAGING & STORAGE

VpCI®-330 is packaged in 5 gallon (19 L) plastic pails, 55 gallon (208 L) metal drums, liquid totes, and bulk.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

VpCI® METALWORKING PRODUCTS



FEATURES

- Non-flammable
- Clear and homogeneous (from at least 40 to 140 °F [4 to 60 °C])
- Contains no chromates, nitrites, phosphates, secondary amines, or OSHA hazardous components

BENEFITS

- Provides universal corrosion protection to ferrous metals and is compatible with yellow metals
- Performs effectively even under the adverse conditions of 100% relative humidity and in the presence of corrosive species such as chlorides
- Easily sprayed using a handheld trigger spray bottle or common spray equipment

APPLICATION

VpCI®-330 can be sprayed, dipped, rolled, or brushed onto metal surfaces. A handheld trigger spray bottle works well for easy application.

VpCI®-330

TYPICAL PROPERTIES

Appearance	Clear Yellow Liquid
Film Type	Transparent Oil Film
Density	6.6-7.0 lb/gal (0.79-0.84 kg/L)
Flash Point	179 °F (82 °C)
Viscosity (104 °F [40 °C])	2.5 cPs

STANDARD TEST METHODS

Test Method	Description	Results
ASTM D1748	Humidity Chamber	>800 hours
ASTM B117	Salt Spray	24 hours
ASTM D130	Copper Strip Test	1a

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC
info@corotecvci.com
<https://www.corotecvci.com>
<https://www.corotecmetalworking.com>



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.