

# VpCI®-372 Peelable Coating

## DESCRIPTION

VpCI®-372 is a fast drying, water-based acrylic peelable coating that provides protection in sheltered applications. Provides multi-metal protection. Excellent UV resistance. Can be matched to some custom colors.

## PACKAGING & STORAGE

VpCI®-372 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) metal drums, liquid totes, and bulk. Keep product from freezing.

Product shelf life is 1 year.



## CHARACTERISTICS/TECHNICAL DATA

Volume Solids	33.40%
Gloss (ASTM D532)	NA
VOCs (ASTM D3960)	0.2 lbs/gal (24 g/l)
Viscosity	50-70 sec # 3 Zahn Cup
Pencil Hardness (ASTM D3363)	NA
Spreading Rate	536 sq.ft./gal @ 1.0 mils DFT (13.15 sq.m/l@25 µm)
Weight per Gallon	8.85 lbs/gal (1.06 kg/l)
Flash Point	>200°F (93°C)
Recommended DFT	2.0-10.0 mils (50-250 µm)
Recommended WFT	6.0-30.0 mils (150-750 µm)
Dry to Touch	1-2 hrs
Dry to Handle	2-3 hrs
Recoat Time	NA
Force Dry	15-20 min @ 150°F (65°C)
Full Cure	3-7 days
Salt Spray (ASTM B117)	168 hrs
Humidity (ASTM D1748)	168 hrs
Adhesion (ASTM D3359)	NA
Flexibility (ASTM D522)	1/2" mandrel (1.27cm)

\*All tests performed after a 7 day cure at ambient temperature

# VpCI®-372 Peelable Coating

## APPLICATION

### Surface Preparation

Substrate should be free of grease, oil, dirt, fingerprints, drawing compounds, rust inhibitors, or any other surface contamination that could affect adhesion. For structural steel applications, Cortec® recommends a minimum of a NACE #3/SSPC-SP6 commercial blast clean. Consult Cortec® and/or test system adhesion prior to full scale application.

**Note: Make sure dew point is more than 5°F (2°C) less than air temperature for application. Power agitate to a uniform consistency using a "squirrel cage" type mixer, hand-held drill mixer, or other equivalent method. VpCI®-372 can be applied by spray, roll, brush, or dip.**

### Typical Equipment Set Ups

#### HVLP / Conventional Spray

- Tip .009"-.021" \*dependent upon pressures and viscosity
- Air Pressure 45-55 psi
- Fluid Pressure 10 psi
- Fluid hose should be 3/8" (0.95 cm) I.D. with a maximum length of 50 feet (15.2 m). Pot should always have dual regulation and be kept at same elevation as spray gun.

#### Air Assisted Airless / Airless

- Tip .015"-.035" \*dependent upon pressures and viscosity
- Pressure 1800-2500 psi
- Hose should be 3/8" (0.95 cm) I.D. minimum, but a 1/4" (0.64 cm) I.D. whip end section may be used for ease of application. A maximum length of 100 feet (30.5 m) is suggested.

### Clean Up

Clean tools/equipment immediately after use with water when coating is still wet. When dry, simply peel off.

**FOR INDUSTRIAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN  
KEEP CONTAINER TIGHTLY CLOSED  
NOT FOR INTERNAL CONSUMPTION  
CONSULT SAFETY DATA SHEET FOR MORE  
INFORMATION**

4119 White Bear Parkway, St. Paul, MN 55110 USA  
Phone (651) 429-1100, Fax (651) 429-1122  
Toll Free (800) 4-CORTEC  
info@cortecvci.com  
http://www.cortecvci.com  
http://www.corteccoatings.com



#### LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

**BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.** No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

**THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.**