



VpCI®-812



PRODUCT DESCRIPTION

VpCI®-812 Wax/Paste is a long-lasting, high-shine wax and rust blocker containing high performance Vapor phase Corrosion Inhibitors (VpCI®). VpCI®-812 Wax/Paste stops corrosion, ultraviolet (UV) rays, and fiberglass oxidation that silently attacks the finish of vehicles beneath the shine.

VpCI®-812 Wax/Paste adds years to the finish of a vehicle or boat. It works on any waxable surface, removing dulling film and oxidation. VpCI®-812 Wax/Paste uses the same tough, long-lasting wax used by professionals.

TYPICAL USES

- Easy application
- Provides excellent durability and resistance to multiple detergent washings
- Easy to buff and rub-out
- Provides excellent long-lasting gloss
- Effectively protects the treated area from UV rays, fiberglass oxidation, and the effects of urban pollution on painted surfaces
- Contains vapor corrosion inhibitors
- Water repellent
- Leaves no waxy chemical build-up on painted surfaces
- Seals metal surfaces against corrosive elements such as air and moisture

APPLICATION

- Cars, motorcycles
- Boats
- House trailers and campers
- Snowmobiles
- Any painted metal surface

METHOD OF APPLICATION

Apply VpCI®-812 Wax/Paste to painted metal surfaces. After the paste dries, buff it off with clean cloth.

VpCI®-812 Wax/Paste can be applied by hand or with a high speed buffer using straight strokes. Do not use excessive pressure.

PHYSICAL PROPERTIES

Appearance	Off-white viscous liquid
Density	8.0-8.1 lb/gal (0.96-0.97 kg/l)
Non-volatile Content	16-20%
Viscosity	8,000-25,000 cps

PACKAGING

VpCI®-812 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk.



**FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT SAFETY DATA SHEET FOR MORE
INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE,

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
<http://www.cortecvci.com>

Printed on recycled paper  100% post consumer

Revised: 05/09/16. Supersedes: 10/09/13. ©Cortec Corporation 2002-2013 of Cortec Corporation.
All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. 2013, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.