

.

•

•

•

.....

•

•

.

•

000

0

0



## 4119 White Bear Parkway, St. Paul, MN 55110 USA Phone: (651) 429-1100, Fax: (651) 429-1122 Toll Free: (800) 4-CORTEC, E-mail: info@cortecvci.com cortecvci.com • corteclaboratories.com **Evaluating Corrosion Preventive Packaging** Systems for GA Manufacturing To: **Bob** Dessauer For: Customer From: Cortec Corporation Laboratories 4119 White Bear Parkway St. Paul, MN 55110 **Boris Miksic** cc: **Cliff Cracauer** Andrew Wroblewski

**Project** #: 14-225-1125.bis

Eine Untala

**Reported by:** 

Eric Uutala Technical Service Manager

U. Rharshow -

**Approved by:** 

Margarita Kharshan Vice President of R&D



**Date:** 12/4/2014

Background:	Customer has been using a packaging system utilizing Zerust film and paper. This system will be tested and compared to VpCI-126 Blue film.
Sample Recei	<b>ved:</b> Two sets of machined metal rings, one wrapped in VpCI-126 blue film, the other wrapped in Zerust Film, with Zerust paper inside.
	*Three swashplates were also sent, but corrosion was seen on one. Therefore, these parts were not tested.
Method:	ASTM D-1735 Water Fog Cabinet
Materials:	Two sets of machined metal rings VpCI-126 Blue Film Zerust Film Zerust Paper
Procedure:	The following procedure was used:
	<ol> <li>All parts were packed by customer prior to testing.         <ul> <li>a. The parts were arranged as follows:                       <ul></ul></li></ul></li></ol>
Results:	The following results were found:

Packaging System	<b>Corroded Parts After 432 Hours</b>
Zerust Film and Paper	12/12
VpCI-126 Blue Film	1/6

**Photos:** See below.



Figure 1: Zerust packaged parts, after 432 hours in ASTM D-1735 testing.



Figure 2: VpCI-126 packed parts, after 432 hours in ASTM D-1735 testing.

**Interpretations:** Customer has been using a packaging system with Zerust film and paper, wrapped around two rows of parts. This packaging system failed on all 12 parts in ASTM D-1735 testing. Parts corroded at different times and to differing amounts throughout the test; the first part showed corrosion after 96 hours.

Conversely, VpCI-126 provided complete protection on 5 of 6 parts. The single part that corroded was in contact with the test chamber itself, and as such, was exposed to constant water contact.